

3M UK PLC
3M HOUSE, PO BOX 1, MARKET PLACE,
BRACKNELL, BERKSHIRE RG12 1JU
Tel: 01344 858000

=====
MATERIAL SAFETY DATA SHEET
=====

Document id : 11-7607-2 Issue date : 2002.01.09
Version : 8.01 Supersedes date : 2001.07.12
Document status : 1

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION

Tradename:

3M (TM) REMOUNT ADHESIVE (UK 9473)

3M Product ID:

GS-2000-1898-3	GS-2000-1903-1	GS-2000-1904-9
GS-2000-1905-6	GS-2000-1906-4	GS-2000-1908-0
GS-2000-1909-8	GS-2000-1910-6	GS-2000-1911-4
GS-2000-1912-2	GS-2000-1913-0	GS-2000-1914-8
GS-2000-1944-5	GS-2000-2051-8	GS-2000-2439-5
GS-2000-2440-3	GS-2000-2441-1	GS-2000-2817-2
GS-2000-2500-4	GS-2000-3350-3	GS-2000-3351-1
GS-2000-3352-9	GS-2000-3353-7	GS-2000-3354-5
GS-2000-3355-2	GS-2000-3356-0	

2 COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient name and classification	CAS number	Percentage
BUTANE	106-97-8	30.0 - 40.0
EU Hazard Symbols and Risk Phrases: F+,T; R:45-46-12		
ACETONE	67-64-1	20.0 - 30.0
EU Hazard Symbols and Risk Phrases: (F,Xi; R:11-36-66-67)		
ISOHEXANE	---	20.0 - 30.0
PROPANE	74-98-6	10.0 - 20.0

3 HAZARDS IDENTIFICATION

Critical hazards:

Extremely flammable. Irritant. Dangerous to environment.
Irritating to eyes and skin. Vapours may cause drowsiness and
dizziness. Toxic to aquatic organisms. May cause long-term
adverse effects in the aquatic environment.

3M (TM) REMOUNT ADHESIVE (UK 9473)

Page 2 of 8 Total Pages

4 FIRST-AID MEASURES

Eye Contact:

Immediately flush eyes with large amounts of water. Get
immediate medical attention.

Skin Contact:

Flush skin with large amounts of water. If irritation persists,
get immediate medical attention.

Inhalation:

Remove person to fresh air. If not breathing, give artificial
respiration. If breathing is difficult, get immediate medical
attention.

Ingestion:

Do not induce vomiting. Drink two glasses of water. Call a
medical doctor.

5 FIRE-FIGHTING MEASURES

Suitable Extinguishing Media:

Water spray, Carbon dioxide, Dry chemical, Foam.

Exposure Hazards:

During Fire: Closed containers exposed to heat from fire may

build pressure and explode. Vapours may travel long distances along the ground or floor to an ignition source and flash back.

Hazardous Decomposition:

Carbon monoxide, carbon dioxide, aldehydes, ketones and hydrocarbons.

Fire-Fighting Procedures:

Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, tunic and trousers (leggings), bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head. Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

6 ACCIDENTAL RELEASE MEASURES

Personal Precautions:

Observe precautions from other sections.

3M (TM) REMOUNT ADHESIVE (UK 9473)

Page 3 of 8Total Pages

Methods for Cleaning up:

Ventilate area. Extinguish all ignition sources. Cover with absorbent material. Collect using non-sparking tools. Place in a suitable metal container.

7 HANDLING AND STORAGE

Precautions for Safe Storage:

Store at temperatures below 49 C.

Fire Prevention:

Aerosol container contains flammable gas under pressure. Extremely flammable liquid and vapour.

Explosion Prevention:

Keep away from heat, sparks, open flame, and other sources of ignition.

Static Prevention:
Avoid static discharge.

Precautions for Safe Handling:
Do not pierce or burn container, even after use.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye Protection:
Avoid eye contact with vapour, spray, or mist. Wear vented goggles or safety glasses with side shields if exposure is likely.

Hand Protection:
Wear appropriate gloves when handling this material. A pair of gloves made from the following materials is recommended: polyethylene/ethylene vinyl alcohol or polytetrafluoroethylene (Teflon).

Skin Protection:
Avoid prolonged or repeated skin contact.

Respiratory Protection:
Avoid inhalation of vapours, mists or spray. Select one of the following respirators based on airborne concentration of contaminants and in accordance with national regulations: Half-mask organic vapour respirator.

Ingestion:
Do not ingest. Keep out of the reach of children.

Recommended Ventilation:
Use in a well-ventilated area. Provide sufficient ventilation to maintain emissions below recommended exposure limits. If exhaust ventilation is not adequate, use appropriate respiratory protection.

Exposure Limits:

BUTANE (106-97-8)
UK HSE TWA: 600 ppm; 1450 mg/m³ OES

UK HSE STEL: 750 ppm; 1810 mg/m3 OES

ACETONE (67-64-1)

UK HSE TWA: 750 ppm; 1810 mg/m3 OES

UK HSE STEL: 1500 ppm; 3620 mg/m3 OES

PROPANE (74-98-6)

UK HSE TWA: Asphyxiant OES

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance and Odour:	Clear liquid in aerosol container
pH:	Not applicable
Boiling point/boiling range:	Not determined
Melting point/melting range:	Not determined
Flash point:	-46.00
Autoflammability:	Not determined
Vapour pressure:	Not determined
Water Solubility:	Not determined
Specific gravity:	Not determined
Vapour density:	Not determined
Volatile organic compounds:	Not determined
Evaporation rate:	Not determined
Viscosity:	Not determined
Percent volatile:	90 %

10 STABILITY AND REACTIVITY

Conditions to Avoid:

Heat.

Materials to Avoid:

Not applicable.

Hazardous Decomposition:

Stable. Hazardous polymerisation will not occur.

11 TOXICOLOGICAL INFORMATION

Effects from Eye Contact:

Moderate Eye Irritation: signs/symptoms can include redness, swelling, pain, tearing, and hazy vision.

Effects from Skin Contact:

Mild Skin Irritation (after prolonged or repeated contact): signs/symptoms can include redness, swelling, and itching. May be absorbed through the skin in harmful amounts.

Effects from Inhalation:

Intentional concentration and inhalation may be harmful or fatal. Central Nervous System Depression: signs/symptoms can include headache, dizziness, drowsiness, incoordination, slowed reaction time, slurred speech, giddiness and unconsciousness. Upper respiratory irritation: signs/symptoms can include soreness of the nose and throat, coughing and sneezing.

Effects from Ingestion:

Ingestion is not a likely route of exposure to this product.

12 ECOLOGICAL INFORMATION

Other Effects and Information:

Not determined.

13 DISPOSAL CONSIDERATIONS

Special Instructions:

Incinerate in a facility licenced to handle hazardous waste and in the presence of a combustible material. Facility must be capable of handling aerosol cans. Dispose of empty cans in a landfill/waste disposal site. Dispose of completely absorbed waste product in a facility permitted to accept chemical wastes. Since regulations vary, consult applicable regulations or authorities before disposal.

3M (TM) REMOUNT ADHESIVE (UK 9473)

Page 6 of 8Total Pages

14 TRANSPORT INFORMATION

UN NUMBER:

UN number: UN1950

UK ROAD/SEA FREIGHT (IMO) CLASSIFICATION:

Substance Identification Number: UN1950

Class: 2.0

Packing Group: Not applicable

Proper Shipping Name: Aerosols

CDG-ROAD (if applicable) Not applicable

ADR/RID CLASSIFICATION:

Class: 2.0

Item Number: 5 F

ICAO/IATA CLASSIFICATION:

Class: 2.1

Sub-Risk: None

Packing Group: Not applicable

Proper Shipping Name: Aerosols Flammable

15 REGULATORY INFORMATION

Precautionary Label Information:

Symbol(s):

Flame (Extremely Flammable) St. Andrew's Cross (Irritant) N
Dangerous to environment.

Risk Phrases:

Extremely flammable. Irritating to eyes and skin. Vapours may cause drowsiness and dizziness. Toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment.

Safety Phrases:

Keep away from heat. Keep away from sources of ignition including pilot lights and sparks. No smoking. Do not breathe vapour or spray. Use only in well ventilated areas. Avoid contact with the skin and eyes. In case of contact with eyes,

3M (TM) REMOUNT ADHESIVE (UK 9473)

Page 7 of 8Total Pages

rinse immediately with plenty of water and seek medical advice. After contact with skin, wash immediately with plenty of water. WARNING! Pressurised container. Protect from sunlight and do not expose to temperatures exceeding 50 degrees C. Do not pierce or burn, even after use. Do not spray on a naked flame or incandescent material. Avoid release to the environment. Refer to special instructions/safety data sheets. Keep out of the reach of children.

16 OTHER INFORMATION

Regulatory Information:

The following UK Regulations as amended may affect the product as supplied:
The Chemicals (Hazard Information and Packaging for supply) Regulations, as amended.
The Carriage of Dangerous Goods (Classification, Packaging and Labelling) and use of

Transportable Pressure
Receptacles Regulations 1996, as
amended.
Carriage of Dangerous Goods by
Road Regulations, 1996, as
amended.
The Petroleum (Consolidation)
Act 1928.
The Control of Substances
Hazardous to Health Regulations
1999 as amended.
The Special Waste Regulations
1996, as amended.
The Environmental Protection
Act, 1990 The Health and Safety
at Work Act, 1974.

Reissue date/Reason for reissue.
Added 3M ID stock numbers.

Intended Use of Product:
A repositionable adhesive in an aerosol dispenser.

The information on this Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law).

The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials.

For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.